



## CC-0530 Hot Melt Adhesive SAFETY DATA SHEET

### SECTION 1: COMPANY INFORMATION

**APPLIED Products, Inc.**  
6035 Baker Road  
Minnetonka, MN 55345  
Phone: 800.365.2480

**Preparation Date:** May 30, 2019  
Rev. 1


**Emergency Contact Number:** CHEMTREC (800) 424-9300

### PRODUCT INFORMATION

**Product Name:** CC-0530  
**Product Description:** Hot Melt Adhesive

### SECTION 2: HAZARDS IDENTIFICATION

**WARNING:** Static charges generated by emptying package in or near flammable vapors may cause ignition. Vapors above molten adhesive may cause eye, skin and respiratory tract irritation. Molten adhesive may cause severe burns. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Pictogram(s)	Hazard Class	Hazard Category
	Skin Irritation	2
	Eye Irritation	2A
	Skin Sensitization	1

### PRECAUTIONARY STATEMENTS

**Prevention:** Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

**Response: IF ON SKIN:** Wash with plenty of soap and water. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

**Storage:** Not prescribed **Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

*Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).*

See Section 11 for additional toxicological information.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Paraffin waxes (petroleum), hydrotreated	64742-51-4	30 - 40
Distillates, petroleum, steam-cracked, polymd.	68131-77-1	5 - 10
Rosin, oligomeric reaction products with isophthalic acid and pentaerythritol	68515-02-6	5 - 10

\*Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### SECTION 4: FIRST AID MEASURES

**Inhalation:** Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.



**Skin contact:** Molten adhesive may cause severe burns. Cool melted product on skin with plenty of water. Do not remove solidified product. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn. Cover affected areas with clean sheeting or gauze and seek immediate medical attention.

**Eye contact:** If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.

**Ingestion:** Ingestion of solid adhesive is not expected to be hazardous. If symptoms develop and persist, get medical attention.

**Symptoms:** See Section 11.

---

## SECTION 5: FIRE FIGHTING MEASURES

**Extinguishing media:** Use extinguishing measures appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide.

**Special firefighting procedures:** Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.

**Unusual fire or explosion hazards:** None.

**Hazardous combustion products:** Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** No special environmental precautions required. Do not allow material to contaminate ground water system.

**Clean-up methods:** Spilled material will solidify. Scrape up spilled material and place in a closed container for disposal. Dispose of contaminated material as waste according to Section 13.

---

## SECTION 7: HANDLING AND STORAGE

**Handling Information:** Always be careful around molten material. Avoid skin contact with molten resins. Follow suggested application temperature. Do not wear contact lenses. At elevated temperatures, irritating fumes may be emitted. Provide adequate ventilation.

**Storage Information:** For safe storage, store between 32°F (0 °C) and 100.4 °F (38 °C)

*For information on product shelf life, please review labels on container or check the Technical Data Sheet.*

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Paraffin waxes (petroleum), hydrotreated	None	None	None	None
Distillates, petroleum, steam-cracked, polymd.	None	None	None	None
Rosin, oligomeric reaction products with isophthali acid and pentaerythritol	None	None	None	None

**Engineering controls:** Work should be done in an adequately ventilated area (i.e., ventilation sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.

**Respiratory protection:** No personal respiratory protective equipment normally required. Where the potential exists for exposure to decomposition products due to heating or elevated temperatures, wear NIOSH approved respiratory protection as appropriate.



**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses.

**Skin protection:** Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Solid

**Odor:** Negligible

**pH:** Not available

**Boiling point/range:** > 428 °F (>220 °C)

**Melting point/ range:** > 158 °F (>70 °C) (Softening Point)

**Specific gravity:** 0.98

**Flash point:** > 428 °F (>220 °C) Cleveland open cup

**Flammable/Explosive limits - lower:** Not applicable

**Flammable/Explosive limits - upper:** Not applicable

**Autoignition temperature:** Not available

**Solubility in water:** Insoluble

**Partition coefficient (n-octanol/water):** Not available

**VOC content:** 0%

**Decomposition temperature:** Not available

**Color:** Yellow

**Odor threshold:** Not available

**Vapor pressure:** Not available

**Vapor density:** Not available

**Evaporation rate:** Not applicable

**Viscosity:** Not available

## SECTION 10: STABILITY AND REACTIVITY DATA

**Stability:** Stable.

**Hazardous reactions:** Will not occur

**Hazardous decomposition products:** Thermal decomposition can lead to release of irritating gases and vapors. Oxides of carbon.

**Incompatible materials:** Oxidizing agents

**Reactivity:** Not available

**Conditions to avoid:** To avoid thermal decomposition, do not overheat. Avoid temperatures above 392°F (200°C)

## SECTION 11: TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### POTENTIAL HEALTH EFFECTS/SYMPTOMS

**Inhalation:** Dusts from solid adhesive may cause irritation. Continuous breathing of vapors above molten adhesive may irritate mucous membranes.

**Skin contact:** Solid adhesive has no hazards. Molten adhesive may cause severe burns.

**Eye contact:** Can cause mechanical irritation if dusts are generated. Fumes released during thermal processing may cause eye irritation. Molten adhesive in eyes will cause severe and permanent damage..

**Ingestion:** Not expected under normal conditions of use. Expected to be low in toxicity.

Hazardous Component(s)	LD50s and LC50s	Immediate & Delayed Health Effects	
Paraffin wax (petroleum), hydrotreated	None	No Records	
Distillates, petroleum, steam-cracked, polymd.	None	Irritant	
Rosin, oligomeric reaction products with isophthalic acid and pentaerythritol	None	No Data	
Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Paraffin wax (petroleum), hydrotreated	No	No	No
Distillates, petroleum, steam-cracked, polymd.	No	No	No



Rosin, oligomeric reaction products with isophthalic acid and pentaerythritol	No	No	No
---	----	----	----

## SECTION 12: ECOLOGICAL INFORMATION

**Ecological information:** Do not empty into drains, soil or bodies of water.

Information provided is for unused product only.

**Recommended method of disposal:** This product is not a RCRA hazardous waste when discarded. Processing, use, or contamination of this product may change the hazard classification and waste management options. Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** Not a RCRA hazardous waste.

---

## SECTION 13: DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** This product is not a RCRA hazardous waste when discarded. Processing, use, or contamination of this product may change the hazard classification and waste management options. Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** Not a RCRA hazardous waste.

---

## SECTION 14: TRANSPORTATION INFORMATION

The transport information provided in this section only applies to the material/formulation itself and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated  
Hazard class or division: None  
Identification number: None  
Packing group: None

### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated  
Hazard class or division: None  
Identification number: None  
Packing group: None

### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated  
Hazard class or division: None  
Identification number: None  
Packing group: None

---

## SECTION 15: REGULATORY INFORMATION

### United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

### Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic



Substances List.

---

**SECTION 16: OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: 9 and 15.

Revision date: 5-30-19

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Applied Products from its suppliers, and because Applied Products has no control over the conditions of handling and use, Applied Products makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information and product are supplied solely for your information and discretionary use, Applied Products assumes no responsibility for reliance or use thereon. It is the responsibility of the user of the product to comply with all applicable federal, state and local laws and regulations.