



CC9161 Hot Melt Adhesive SAFETY DATA SHEET

SECTION 1: COMPANY INFORMATION

APPLIED Products, Inc.
6035 Baker Road
Minnetonka, MN 55345
Phone: 800.365.2480

Preparation Date: September 18, 2017

Emergency Contact Number: CHEMTREC (800) 424-9300

PRODUCT INFORMATION

Product Name: CC9161
Product Description: Hot Melt Adhesive

SECTION 2: HAZARDS IDENTIFICATION

Molten adhesive may cause severe burns. Static charges generated by emptying package in or near flammable vapors may cause ignition. Vapors above molten adhesive may cause eye, skin and respiratory tract irritation.

Pictogram(s) None	Hazard Class	Hazard Category
	None	None

PRECAUTIONARY STATEMENTS

Prevention: Not prescribed	Response: Not prescribed
Storage: Not prescribed	Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Paraffin waxes and hydrocarbon waxes	8002-74-2	20 - 30
1-Octene, polymer with ethene	26221-73-8	20 - 30

**Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.*

SECTION 4: FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Molten adhesive may cause severe burns. Cool melted product on skin with plenty of water. Do not remove solidified product. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn. Cover affected areas with clean sheeting or gauze and seek immediate medical attention.

Eye contact: If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.

Ingestion: Ingestion of solid adhesive is not expected to be hazardous. If symptoms develop and persist, get medical attention.

Symptoms: See Section 11.



SECTION 5: FIRE FIGHTING MEASURES

Extinguishing media: Use extinguishing measures appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide.

Special firefighting procedures: Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.

Unusual fire or explosion hazards: None.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: No special environmental precautions required. Do not allow material to contaminate ground water system.

Clean-up methods: Spilled material will solidify. Scrape up spilled material and place in a closed container for disposal.

SECTION 7: HANDLING AND STORAGE

Handling Information: Always be careful around molten material. Avoid skin contact with molten resins. Follow suggested application temperature. Do not wear contact lenses. At elevated temperatures, irritating fumes may be emitted. Provide adequate ventilation.

Storage Information: For safe storage, store between 32°F (0 °C) and 100.4 °F (38 °C)

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Paraffin waxes and Hydrocarbon waxes	2 mg/m ³ TWA Fume	None	None	None
1-Octene, polymer with ethene	10 mg/m ³ TWA Inhalable particles. 3 mg/m ³ TWA Respirable particles.	15 mg/m ³ PEL Total dust. 5 mg/m ³ PEL Respirable fraction. 15 MPPCF TWA Respirable fraction. 5 mg/m ³ TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 50 MPPCF TWA Total dust.	None	None

Engineering controls: Work should be done in an adequately ventilated area (i.e., ventilation sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.

Respiratory protection: No personal respiratory protective equipment normally required. Where the potential exists for exposure to decomposition products due to heating or elevated temperatures, wear NIOSH approved respiratory protection as appropriate. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses.

Skin protection: Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical state: Solid	Color: Light Yellow
Odor: Negligible	Odor threshold: Not available
pH: Not available	Vapor pressure: Not available
Boiling point/range: > 428°F (>220°C) Cleveland open cup	Melting point/ range: 248°F (120°C)
Specific gravity: 0.96	Vapor density: Not available
Flash point: > 428°F (>220°C) Cleveland open cup	Flammable/Explosive limits - lower: Not applicable
Flammable/Explosive limits - upper: Not applicable	Autoignition temperature: Not applicable
Evaporation rate: Not applicable	Solubility in water: Insoluble
Partition coefficient (n-octanol/water): Not available	VOC content: 0%
Viscosity: Not available	Decomposition temperature: Not available

SECTION 10: STABILITY AND REACTIVITY DATA

Stability: Stable.	
Hazardous reactions: Will not occur	
Hazardous decomposition products: Thermal decomposition can lead to release of irritating gases and vapors. Oxides of carbon.	
Incompatible materials: Oxidizing agents	Reactivity: Not available
Conditions to avoid: To avoid thermal decomposition, do not overheat. Avoid temperatures above 392°F (200°C)	

SECTION 11: TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

POTENTIAL HEALTH EFFECTS/SYMPTOMS

Inhalation: Dusts from solid adhesive may cause irritation. Continuous breathing of vapors above molten adhesive may irritate mucous membranes.

Skin contact: Solid adhesive has no hazards. Molten adhesive may cause severe burns.

Eye contact: Can cause mechanical irritation if dusts are generated. Fumes released during thermal processing may cause eye irritation. Molten adhesive in eyes will cause severe and permanent damage..

Ingestion: Not expected under normal conditions of use. Expected to be low in toxicity.

Hazardous Component(s)	LD50s and LC50s	Immediate & Delayed Health Effects
Paraffin wax and Hydrocarbon waxes	None	Irritant
1-Octene, polymer with ethene	None	No Records

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Paraffin wax and Hydrocarbon waxes	No	No	No
1-Octene, polymer with ethene	No	No	No

SECTION 12: ECOLOGICAL INFORMATION

Ecological information: Do not empty into drains, soil or bodies of water.



SECTION 13: DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: This product is not a RCRA hazardous waste when discarded. Processing, use, or contamination of this product may change the hazard classification and waste management options. Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

SECTION 14: TRANSPORTATION INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

SECTION 15: REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312: None

CERCLA/SARA Section 313: None above reporting de minimis

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

SECTION 16: OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Applied Products from its suppliers, and because Applied Products has no control over the conditions of handling and use, Applied Products makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information and product are supplied solely for your information and discretionary use, Applied Products assumes no responsibility for reliance or use thereon. It is the responsibility of the user of the product to comply with all applicable federal, state and local laws and regulations.