

**TYPE OF ADHESIVE:**

Synthetic Polymer

**FIELD OF APPLICATION:**

Bottle Labeling

**TYPICAL TECHNICAL DATA**

Viscosity 70,000 cps

(Brookfield spindle #7 @ 20 RPM @ 76°F)

pH 8.8

Density 9.2 lbs/gallon

Color Off White, viscous liquid. Dry film is clear

Solids 38%

Application 70°F to 85°F

**PROPERTIES:**

AQUENCE XP 7010 is a high performance labeling adhesive for glass containers needing hyper-condensation resistance. AQUENCE XP 7010 was developed to replace Casein based labeling adhesives on very cold and wet bottles. The product exhibits excellent machinability on high-speed rotary labelers. AQUENCE XP 7010 patterns well, which offers higher mileage versus conventional Casein products. AQUENCE XP 7010 will pass brewery ice proof tests (7 day cure, 72 hour soak).

**HANDLING AND APPLICATION:**

Supplied ready for use. Meets FDA Section 175.105 for indirect food contact. Clean up wet or dry adhesive with water.

**PRECAUTIONS:**

To avoid accidental contamination, keep container covered when not in use.

**STORAGE CONDITIONS:**

Keep from freezing.

Shelf life is 6 months.

**Note**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all marks used are trademarks of Henkel or its affiliates in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.