



Swift[®] tak 17003 Aqueous Adhesive

Suggested Application

17003 was developed specifically for corewinding operations which require excellent wet tack.

APPLICATION METHOD: Wheel

Typical Properties

Color	White
Viscosity @79 °F (26 °C)	2,300 - 2,800 cps
Solids	31 - 37 %
pH	4.0 - 6.0

Features & Benefits

Excellent Machining	Fast clean-up / minimal build-up during shutdowns.
Excellent Wet Tack	Eliminates "dog ears" on line.
Excellent Adhesion	Good adhesion to a wide variety of substrates.

Packaging Forms

5 gallon pails, 55 gallon drums and 300 gallon totes. Other packaging may be available.

Storage

For best performance, the product should be stored and used at 65 - 85 °F. **Do not freeze.** Ship and store at temperatures above 5 °C. Shelf life is 6 months maximum in closed containers.



H.B. Fuller



TECHNICAL DATA SHEET

Clean Up

Best to clean before drying. Use warm water.

Important Safety Information

Avoid contact with skin and eyes. Product will irritate eyes if contact occurs. Skin irritation is possible on prolonged or repeated contact.

Before using this or any other chemical product, be sure to read and understand the information on the Material Safety Data Sheet and Product Labels. Remain aware of potential hazards and follow all precautionary measures, handling instructions, and disposal considerations outlined in the MSDS and labels.

For help in a Chemical Emergency, call CHEMTREC at 1-800-424-9300.

Rev 07/10

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the **H.B. Fuller General Terms and Conditions of Sale** applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, **the total aggregate liability of H.B. Fuller** for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is **limited to replacement of affected products or refund of the purchase price for affected products.** H.B. Fuller **shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses** arising out of or in connection with product supply.



H.B. Fuller

H.B. Fuller North America
inquiry@hbfuller.com
Contact us details