

Professional Grade Anti-Seize Lubricants



Introducing
GorillaPro®



APPLIED is proud to distribute GorillaPro® products.



Bring the Heat

GorillaPro ultra-premium anti-seize compounds are used on threads, bolted joints, and as a protective barrier between two metal surfaces that can reach very high temperatures. They convert torque to tightening force more efficiently, and protect threads or surfaces from seizing and galling, even under extremely stressful environments. Their blends of nickel or copper and graphite lubricants allow for easy disassembly of mechanical parts.

GorillaPro anti-seize compounds are highly refined, heavy-duty, high-temperature lubricants that provide a barrier between metal surfaces.

To learn more or to purchase, visit
appliedadhesives.com/gorillapro

BENEFITS

- Copper and nickel formulas
- Protects bolt and pipe threads from seizing, galling, and cold welding
- Lubricates and seals threads
- Resists rust and corrosion
- Allows for easy disassembly in corrosive or hot environments
- Handy brush-top applicator



Brute Strength. Professional Grade.™

Professional Grade Anti-Seize Lubricants

GorillaPro® anti-seize compounds are used on threads, bolts, fasteners, flanges, and other clamped interfaces. They prevent the threads or two metal surfaces from seizing and galling and allows for easy disassembly. Designed to convert torque to tightening force more efficiently, anti-seize is formulated with high solids content and a carrier grease. But unlike grease, the solid lubricant withstands high temperatures and protects parts even under extremely stressful environments.



COPPER

NSCU



Premium Copper-Based Anti-Seize Lubricant

RUST PROTECTION: Protects parts from seizing and rusting together

MAINTENANCE FREE: Greatly reduces maintenance challenges caused by parts rusting together

REMOVABLE: Aids in assembly and disassembly of parts

CORROSION RESISTANT: Highly resistant to saltwater corrosion and galvanic corrosion

HEAT RESISTANT: Withstands temperatures up to 1800°F

VERSATILE: Compatible with all types of metals

COST SAVING: Replaces clamp rings, set screws, and snap rings



NICKEL

NSNI



Nickel-Based Extreme Service Anti-Seize Lubricant

SAFEGUARD: Offers maximum protection from acids, caustics, corrosive chemicals, and extreme heat

PROTECTION: Eliminates seizing and galling of metals up to 2600°F

LUBRICATION: Reduces friction and lowers torque

BARRIER: Provides nickel plating as a barrier between metal surfaces

CORROSION RESISTANT: Protects against corrosion and oxidation

HEAT RESISTANT: Withstands temperatures up to 2600°F

FAST: Speeds assembly and disassembly

Built to Withstand Extreme Environments

Anti-seize is typically used on bolted joints that experience high-temperature environments and require future maintenance. They can also be used to improve gasket performance, provide a more consistent clamp load, prevent galling, improve electrical conductivity, and protect against harsh corrosive environments.

- Reduces friction on stainless steel threads and press fits
- Coats gaskets in high-temperature applications
- Protection from acids, ammonia, acetylene and more

High-Performance MRO Solutions

Proactive maintenance can help prevent costly unplanned downtime. It's a challenge keeping up with maintenance activities while keeping teams trained, equipment operating, and driving productivity. With a full complement of maintenance adhesives, repair epoxies, lubricants, and sealants, GorillaPro can repair and improve the reliability of almost any piece of equipment or machinery.

What's in Your Toolbox?™

IMPORTANT: The information contained herein is believed to be correct to the best of our knowledge. However the recommendations and suggestions herein are made without guarantee or representation as to results. It is the purchaser's responsibility to test and determine the suitability of the product for the purchaser's intended use and purpose. Purchaser assumes all risk and liability whatsoever regarding such suitability. Any product samples provided for testing are provided in accordance with standard limited warranties as stated on our technical data sheets.

Unless otherwise noted, trademarks are property of H.B. Fuller Company or one of its affiliated entities. Gorilla and GorillaPro are registered trademarks of The Gorilla Glue Company. © H.B. Fuller Company, 2020.

Sales Sheet - Anti-Seize Lubricants - Updated 11-05-2021



appliedadhesives.com/gorillapro

6035 Baker Road • Minnetonka, MN 55345

SUPPORT: 1-800-274-9801 • gorillapro@appliedproducts.com



H.B. Fuller