

Brute Strength. Professional Grade.™

Introducing **GorillaPro®**

APPLIED is proud to distribute GorillaPro® products.



High-Performance MRO Solutions

Proactive maintenance can help prevent costly unplanned downtime. It's a challenge keeping up with maintenance activities while keeping teams trained, equipment operating, and driving productivity. With a full complement of maintenance adhesives, repair epoxies, lubricants, and sealants, GorillaPro can repair and improve the reliability of almost any piece of equipment or machinery.



Threadlockers

Keep threaded fasteners from loosening due to shock or vibration. GorillaPro threadlockers prevent rust and corrosion between fastener threads after assembly in high humidity or water contact conditions and provide protection in harsh environments.



Retaining Compounds

Simplify assemblies. Fill gaps between components. Reduce or eliminate expensive machining operations. Prolong equipment life. GorillaPro retaining compounds help your machines run more efficiently and reliably.



Gaskets & Sealants

Protect critical components. Prevent liquid and gas leaks from escaping threaded or flanged fittings. Avoid catastrophic equipment failure. GorillaPro thread sealant and gasket maker prevents leaks and downtime.



Instant Adhesives

The right adhesives for any job. With high strength formulas and quick set time, GorillaPro is the go-to instant adhesive for a variety of industrial fixes. Our instant adhesives are crazy tough. We hang our hard hat on it.



Epoxies & Urethanes

GorillaPro structural adhesives suit a huge array of applications and operating conditions, offering exceptional chemical and heat resistance, adhesion and water resistance, and mechanical and electrical insulating properties.



Anti-Seize Lubricants

GorillaPro anti-seize compounds are highly refined, heavy-duty, high-temperature lubricants that provide a barrier between metal and plastic surfaces and prevent galling, seizure, and corrosion in extremely stressful environments.



To learn more or to purchase, visit appliedadhesives.com/gorillapro

Brute Strength. Professional Grade.™

Product Comparison Guide

No matter what brand you're currently using, this handy product comparison guide will help you find the right GorillaPro® adhesive, sealant, or lubricant for your application. We're here to make it easier for you to use our products for faster repair times, reduced downtime, and extended equipment life.

GorillaPro®	HENKEL® LOCTITE®	3M® Scotch-Weld®	ILLINOIS TOOL WORKS INC. PERMATEX®	ND INDUSTRIES® Vibra-TITE®
Instant Adhesives				
● CA30	495™	PR40 / CA7	49450	395
● CA100	404™ / 414™	PR100 / CA8	40413 / Zip Grip® GPE 100	314
● CA-GEL	454™	SI Gel	SEG	354
○ CA120SI	401™	SI100	SE100	301
● CA500RT	380™	RT5000B	TE100	388
Epoxies & Urethanes				
● EP3	EA E-00CL/100CL™	DP100	5 MINUTE® EPOXY	905
● EP5	EA E-00NS™	DP100NS	GEL 5 MINUTE® EPOXY	910G
● PU5	UK U-05FL™	EC-3532 B/A	Devcon® DEV-THANE™ 5	N/A
Anti-Seize Lubricants				
● NSCU	LB 8008™ C5-A®	08945	COPPER ANTI-SEIZE LUBRICANT	9071
● NSNI	LB 771™	N/A	NICKEL ANTI-SEIZE	9072
Gaskets & Sealants				
○ AS10	567™	PS67	56750	460
● AG101	515™	GM15	51531	732
Retaining Compounds				
● AR200	609™	RT09	60950	530
● AR250	680™	RT80	68050	541
Threadlockers				
● AT75	242™ / 243™	TL42	24250	121
● AT150	262™ / 263™	TL62	26250	131
● AT160	271™	TL71	27150	140
● AT60GEL	248™	N/A	Gel Twist™ 24010	125
● AT105GEL	268™	N/A	Gel Twist™ 27010	135

What's in Your Toolbox?™



IMPORTANT: The information contained herein is believed to be correct to the best of our knowledge. However the recommendations and suggestions herein are made without guarantee or representation as to results. It is the purchaser's responsibility to test and determine the suitability of the product for the purchaser's intended use and purpose. Purchaser assumes all risk and liability whatsoever regarding such suitability. Any product samples provided for testing are provided in accordance with standard limited warranties as stated on our technical data sheets.

Unless otherwise noted trademarks are property of H.B. Fuller Company or one of its affiliated entities. Gorilla and GorillaPro are registered trademarks of The Gorilla Glue Company. Henkel is a registered trademark of Henkel AG & Co. KGaA. Loctite and C5-A are registered trademarks of Henkel IP & Holding GmbH. 495, 404, 414, 454, 380, EA E-00CL/100CL, EA E-00NS, UK U-05FL, LB 8008, LB 771, 567, 515, 609, 680, 242, 243, 262, 263, 271, 248 and 268 are trademarks of Henkel Corporation. Permatex, Zip-Grip, Devcon, 5 Minute and Gel 5 minute are registered trademarks of Illinois Tool Works Inc. Dev-Thane and Gel Twist are trademarks of Illinois Tool Works Inc. 3M and Scotch-weld are registered trademarks of 3M Company. ND Industries and Vibra-Tite are registered trademarks of ND Industries, Inc. © H.B. Fuller Company, 2022.

Cross Reference Sheet - Updated 02-01-2022



appliedadhesives.com/gorillapro

6035 Baker Road • Minnetonka, MN 55345

SUPPORT: 1-800-274-9801 • gorillapro@appliedproducts.com



H.B. Fuller